

SB-3 SAFETY BEAM

LEES TECH
www.leestech.com

The SB-3 SAFETY BEAM is used as a safety device when fitted in conjunction with garage doors, roller doors, sliding gates, swinging gates and parking barriers

FEATURES

- Enclosed in a weatherproof IP65 enclosure the SB-3 Safety Beam is insensitive to ambient light and resistant to tampering by unauthorised personnel
- SB-3 Safety Beam can be installed indoors or outdoors
- SB-3 transmitter and receiver are mounted in line of sight at a maximum distance of 10m apart. No calibration or sensitivity adjustments are necessary
- When the infrared beam is broken the relay de-energises. As the relay de-energises when the beam is broken (or the beam is not present as the result of a fault) the unit operates in the **FAIL-SAFE** mode
- An LED indicator illuminates when the transmitter and receiver are aligned providing a valuable aid to correct installation and fault location



Supply: 12 - 24V AC/DC
Relay Contacts: 5A 30V AC/DC
Dimensions: 110mm (H) x 80mm (W) x 65mm (D)

LEES TECHNOLOGY NZ LTD

3E Tait Place, Albany, Auckland 0632, New Zealand
Tel: 09 447 1093 | Fax: 09 447 1094 | Mobile: 021 737 962
info@leestech.com

Digi-Code

LEES TECH
www.leestech.com

Motorpol